



AUTO COOL ESSENTIAL -25°C

Ready to use cooling liquid, anti-corrosion & antifreeze, protection -25°C / -13°F
Nitrite free / Amine free / Phosphate free / Silicate free / Borate free

USO

MOTUL AUTO COOL ESSENTIAL -25°C is a ready to use cooling liquid, four seasons, based on monoethyleneglycol, using organic additives.

Recommended for all liquid cooling systems: passenger cars, heavy duty, construction and agriculture vehicles, gardening, ships, stationary engines ...

PRESTACIONES

NORMAS	AFNOR NF R 15-601
	AS Standards AS 2108
	ASTM STANDARD D3306
	BRITISH STANDARD BS 6580
	China Standards GB 29743
	Cuna Standards NC 956-16 / NC 956-18
	SAE J1034
	UNE STANDARD 26-361-88/1

Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.

Protects the cooling system from freezing and metallic parts from corrosion.

Provides an excellent thermal exchange and increase engine cooling efficiency.

Seals, rubber pipes and plastic parts friendly.

RECOMENDACIONES

Ready to use, do not add any water.

Drain intervals: Refer to the manufacturers' recommendation.

Do not mix with non-organic products.

This product should not be used to protect drinking water systems against freezing.

Nos reservamos el derecho de modificar las características generales de nuestros productos para ofrecer a nuestros clientes el beneficio de los últimos avances tecnológicos. Las especificaciones serán definitivas desde la realización del pedido, sujeto a nuestras condiciones generales de venta y garantía. 02/25

Motul Iberica S.A Sucursal Colombia - Av. Cra 9 #115-06 Of. 905-906, Edificio Tierra Firme - 110111 - Bogota - +57 1 4325359 - +57 1 4325359 -

info@co.motul.com -

motul.com



AUTO COOL ESSENTIAL -25°C

Ready to use cooling liquid, anti-corrosion & antifreeze, protection -25°C / -13°F
Nitrite free / Amine free / Phosphate free / Silicate free / Borate free

Attention, control or drain the coolant only when the engine is cold.
Dangerous. Respect the use and handling recommendations.

PROPIEDADES

Color	Visual	Verde/Azul
Densidad a 20 °C	ASTM D5931	1.056
Punto congelación	ASTM D97	-27.0 °C / -17.0 °F
pH	ASTM D1287	8.5
Cristalización inicial	ASTM D1177	-24.0 °C / -11.0 °F
Protección contra la congelación		-25.0 °C / -13.0 °F
Punto de ebullición	ASTM D1120	109.0 °C / 228.0 °F