

**Ready to use VW cooling liquid**  
**Anti-corrosion & antifreeze**  
**Protection -37°C / -35°F**  
**Technology Lobrid Tech**

## TYPE OF USE

MOTUL AUTO COOL G12 EVO -37°C is a ready to use long life cooling liquid, based on monoethylene glycol, using an hybrid organic / non organic mix additive technology type Si-OAT, named Lobrid Tech.  
Especially developed for liquid cooling systems of VAG group (VOLKSWAGEN, AUDI, SKODA and SEAT) passenger cars and light duty vehicles when coolant meeting requirements of G12 EVO standard (VW TL 774 L) is required.

## PERFORMANCES

PERFORMANCES VW TL-774 L = G 12 EVO, AUDI TL-774 L = G 12 EVO, SKODA TL-774 L = G 12 EVO,  
SEAT TL-774 L = G 12 EVO

**Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.**

Optimal protection of VAG group engine cooling systems. The Lobrid technology brings optimal protection for all engine metallic parts including aluminum and non-ferrous components. High performance additives protect against freezing, over-heating, corrosion and scale.

This Lobrid technology is recommended for VW G13 (VW TL 774 J) specification and is compatible with coolants meeting former specifications: G12 (VW TL 774 D), G12+ (VW TL 774 F), G12++ (VW TL 774 G) and G13 (VW TL 774 J).

Provides aluminum reinforced protection at high temperature. Eliminates the risk of scaling and deposits in the cooling system. Avoids cavitation and increases water pump lifetime.

Compatible with gaskets, hoses, and plastic components.

Can be mixed with ethylene glycol based coolants.

## RECOMMENDATIONS

Ready to use, do not add any water.

To be used for top-up or complete renewal of the cooling circuit for improved efficiency.

Drain intervals: Refer to the manufacturers' recommendation.

Attention, control or drain the coolant only when the engine is cold.

Can be mixed with ethylene glycol based coolants.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



## MOTUL AUTO COOL G12 EVO -37

**Ready to use VW cooling liquid**  
**Anti-corrosion & antifreeze**  
**Protection -37°C / -35°F**  
**Technology Lobrid Tech**

This product should not be used to protect drinking water systems against freezing.  
Dangerous. Respect the use and handling recommendations.

### PROPERTIES

Color	Visual	Pink
Density at 20°C (68°F)	ASTM D1121	1.073
pH	ASTM D1287	8.2
Initial crystallization	ASTM D1177	-36.0 °C / -33.0 °F
Freezing protection		-37.0 °C / -35.0 °F
Boiling point	ASTM D1120	136.0 (+1.5 bar) °C / 277.0 (+1.5 bar) °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.