



MOTUL AUTO COOL G13 -30°C

Ready to use Cooling Fluid

DESCRIPTION

MOTUL AUTO COOL G13 -30°C is a ready to use long life cooling liquid, based on mono-ethylene glycol and glycerol, using an hybrid organic / non organic mix additive technology, named Lobrid Tech.

Especially developed for liquid cooling systems of VAG group (VOLKSWAGEN, AUDI, SKODA and SEAT) passenger cars and light duty vehicles when coolant meeting requirements of G13 standard (VW TL 774 J) is required.

APPLICATIONS

Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.

Optimal protection of VAG group engine cooling systems. The Lobrid technology brings optimal protection for all engine metallic parts including aluminum and non-ferrous components. High performance additives protect against freezing, overheating, corrosion and scale.

Lobrid technology meets the requirements of G13 (VW TL 774 J) specifications and is compatible with coolants meeting former specifications: G12 (VW TL 774 D), G12+ (VW TL 774 F), G12++ (VW TL 774 G).

Provides reinforced aluminum protection at high temperatures. Eliminates the risk of scaling and deposits in the cooling system. Avoids cavitation and increases water pump lifetime.

Compatible with gaskets, hoses, and plastic components.

Can be mixed with ethylene glycol based coolants.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.