



**Ready to use cooling liquid / Anti-corrosion & antifreeze  
Protection -25°C / -13°F  
Technology Hybrid Tech  
Nitrite free / Amine free / Phosphate free**

## TYPE OF USE

MOTUL AUTO COOL MULTI -25°C is a ready to use long life cooling liquid, based on monoethyleneglycol, using hybrid organic / non organic mix additive technology, named Hybrid Tech.

Compatible with all cooling fluids, this product can be mixed with all monoethyleneglycol based coolants and makes it perfect for top-up.

Recommended for all cooling systems: Gasoline and Diesel engines of passenger cars, heavy duty, construction and agriculture vehicles, gardening, boats, stationary engines, ...

## PERFORMANCES

STANDARDS AND MANUFACTURER SPECIFICATIONS: Refer to chart.

**Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.**

Protects the cooling system and metallic parts from freezing and corrosion.

Facilitates heat transfers for improved engine performance.

Provides an excellent thermal exchange and therefore improves engine cooling efficiency.

Both silicates and organic acids provide anti-corrosion properties that remain while aging.

Seals, hoses, pipes and plastic parts friendly.

## RECOMMENDATIONS

Ready to use, do not dilute, do not add any water.

Drain intervals: Refer to the manufacturers' recommendation.

Attention, control or drain the coolant only when the engine is cold.

This product should not be used to protect drinking water systems against freezing.

Dangerous. Respect use and handling recommendations.



## AUTO COOL MULTI -25



Ready to use cooling liquid / Anti-corrosion & antifreeze  
Protection -25°C / -13°F  
Technology Hybrid Tech  
Nitrite free / Amine free / Phosphate free

### PROPERTIES

Color	Visual	Green Fluo
Density at 20°C (68°F)	ASTM D4052	1.061
pH	ASTM D1287	8.6
Freezing point	NFT 78102	-25.0 °C / -13.0 °F
Boiling point	NFR 15602-4	106.0 °C / 223.0 °F



## AUTO COOL MULTI -25



Ready to use cooling liquid / Anti-corrosion & antifreeze  
Protection -25°C / -13°F  
Technology Hybrid Tech  
Nitrite free / Amine free / Phosphate free

STANDARDS	
ASTM STANDARD	1515087958456, 1517504516350
BRITISH STANDARD	1575455712953
FRENCH STANDARD	1515406344288
FVV STANDARD	1515088046614
JAPANESE STANDARD	1517503929739
KOREAN STANDARD	1515088104334
MIL STANDARD	1515406851383, 1517492552474, 1517492578193, 1517492598631, 1517492622912
NATO	1515088207477
SAE	1515407026224
SWISS FED. LAB	1515407053551
OE PERFORMANCES	
	1515404892643
	1515404954191
	1515405056053
	1515405121523, 1518096829849
	1515405228244
	1515405272260
	1515405337902
	1518015711990, 1518015711990
	1517394372468, 1517394550250
	1517394372468
	1519826681659
	1515405542235
	1515405600220
	1515405748630
	1578322826391
	1515405956275
	1515405853570
	1515406151702
	1515405992026
	1515405914743
PRODUCTS	
JALOS	1578392108015

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com