



## MOTUL AUTO COOL OPTIMAL ULTRA

**Concentrated antifreeze  
Anti-corrosion & antifreeze  
Technology Organic Tech  
Nitrite free / Amine free / Phosphate free / Borate free / Silicate  
free**

### TYPE OF USE

MOTUL AUTO COOL OPTIMAL ULTRA is a concentrated long life antifreeze that should be mixed with soft water for immediate use as a cooling liquid, based on monoethyleneglycol, using an Organic Acid Technology (OAT) additivition named Organic Tech.

Strongly recommended for all cooling systems: passenger cars, heavy duty, construction and agriculture vehicles, gardening, ships, stationary engines ...

### PERFORMANCES

STANDARDS AND MANUFACTURER SPECIFICATIONS: Refer to chart.

Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.

Optimal protection of cooling systems against freezing and metallic parts against corrosion.

OAT technology provides an excellent thermal exchange and therefore improves engine cooling efficiency and prevents from boiling.

This organic technology provides anti-corrosion properties that remain at high temperature and aging. Low corrosion inhibitors consumption allows extended drain intervals.

Water pump protection, avoids cavitation.

Seals, rubber pipes, hoses and plastic parts friendly.



## MOTUL AUTO COOL OPTIMAL ULTRA

**Concentrated antifreeze  
Anti-corrosion & antifreeze  
Technology Organic Tech  
Nitrite free / Amine free / Phosphate free / Borate free / Silicate  
free**

### RECOMMENDATIONS

PROTECTION		AUTO COOL OPTIMAL ULTRA
T °C / T °F	T °C / T °F*	%
-22°C / -8°F	132°C / 269°F	33%
-30°C / -22°F	134°C / 273°F	40%
-41°C / -42°F	136°C / 277°F	50%
-54°C / -65°F	139°C / 282°F	60%

\* +1,5 Bar

Do not use pure product.

Mix with soft water according to the required freezing protection: refer to chart.

To maintain anti-corrosion properties, do not dilute below 33%.

Water for dilution: If possible, use soft water: Maximum hardness 35°F and chlorides and sulfates maximum contain 500 ppm.

Drain intervals: Refer to the manufacturers' recommendation.

Attention, control or drain the coolant only when the engine is cold.

Do not mix with non-organic products.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - [www.motul.com](http://www.motul.com)

[motul.com](http://motul.com)

04/25



## MOTUL AUTO COOL OPTIMAL ULTRA

**Concentrated antifreeze  
Anti-corrosion & antifreeze  
Technology Organic Tech  
Nitrite free / Amine free / Phosphate free / Borate free / Silicate  
free**

This product should not be used to protect drinking water systems against freezing.  
Dangerous. Respect the use and handling recommendations.

### PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D4052	1.112
Sulfated Ash	ASTM D1119	% weight 1.10
Alkalinity reserve	ASTM D1121	6.2 mg KOH/g
Boiling point	ASTM D1120	180°C / 356°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

**Concentrated antifreeze**  
**Anti-corrosion & antifreeze**  
**Technology Organic Tech**  
**Nitrite free / Amine free / Phosphate free / Borate free / Silicate free**

STANDARDS	
ASTM STANDARD	D3306, D4656
BRB	BR 637
BRITISH STANDARD	BS 6580
FVV STANDARD	Germany FVV Heft R443
UNE STANDARD	26-361-88/1
OEM PERFORMANCES	
AUDI	TL-774 D = G 12, TL-774 F = G 12+
CUMMINS	32-9011, IS series & N14
DAF	74002
DETROIT DIESEL	Power Cool Plus
DEUTZ	0199-99-1115, 0199-99-2091
FIAT	9.55523
FORD	WSS-M97B44-D
GENERAL MOTORS	GM 6277M (+B040 1065)
JAGUAR LAND ROVER	CMR 8229, WSS-M97B44-D
JOHN DEERE	JDM H5
KOMATSU	07.892 (2007)
LAND ROVER	CMR 8229, WSS-M97B44-D, WSS-M97B44-D
LEYLAND	DW03245403
LIEBHERR	MD1-36-130
MAN	324 typ SNF, D36 5600
MAZDA	MEZ MN 121 D
MERCEDES-BENZ	MB 325.3
MINI	JQ07913-014
MTU	MTL 5048
MWM	0199-99-2091
NISSAN	Renault 41-01-001/--S Type D
OPEL	GM 6277M (+B040 1065), QL 130100
RENAULT	41-01-001/--S Type D
SAAB	GM 6277M (+B040 1065)
SEAT	TL-774 D = G 12, TL-774 F = G 12+
SKODA	61-0-0257, TL-774 D = G 12, TL-774 F = G 12+
VAUXHALL	GM 6277M (+B040 1065), QL 130100
VOLVO	128 6083 / 002
VW	TL-774 D = G 12, TL-774 F = G 12+
WÄRTSILÄ	32-9011
PRODUCTS	
MAK	A4.05.09.01
SACM DIESEL	DLP799861

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.