

AUTO COOL TYP D -25



Ready to use RENAULT cooling liquid / Anti-corrosion & anti-

freeze

Protection -25°C / -13°F

Technology Organic Tech

Nitrite free / Amine free / Phosphate free / Borate free / Silicate

free

TYPE OF USE

MOTUL AUTO COOL TYPE D -25°C is a ready to use long life cooling liquid, based on monoethyleneglycol, using organic additives (OAT – Organic Acid Technology) using an Organic Acid Technology (OAT) additivation named Organic Tech. Specifically developed for all liquid cooling systems of RENAULT Group passenger cars (Renault, Dacia and Samsung) when coolant meeting requirements of Renault Type D standard is required.

PERFORMANCES

PERFORMANCES

RENAULT 41-01-001/--S Type D

Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.

Specifically developed to meet the requirements of TYPE D standard recommended by the RENAULT Group (Renault, Dacia and Samsung).

Long lasting protection of cooling systems against freezing, corrosion and scale. Optimal protection of aluminum at high temperatures.

OAT coolant technology provides an excellent thermal exchange and therefore improves engine cooling efficiency and prevents from boiling.

This organic technology provides anti-corrosion properties that remain at high temperature and aging. Low corrosion inhibitors consumption allows extended drain intervals.

Water pumps and components protection, avoids cavitation.

Seals, hoses, pipes and plastic parts friendly.

Dangerous. Respect the use and handling recommendations.

RECOMMENDATIONS

Ready to use, do not add any water.

Drain intervals: Refer to the manufacturers' recommendation.

Do not mix with non-organic products.

This product should not be used to protect drinking water systems against freezing.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE
MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



AUTO COOL TYP D -25



Ready to use RENAULT cooling liquid / Anti-corresion & anti-

freeze

Protection -25°C / -13°F

Technology Organic Tech

Nitrite free / Amine free / Phosphate free / Borate free / Silicate

free

Attention, control or drain the coolant only when the engine is cold.

Dangerous. Respect the use and handling recommendations.

PROPERTIES

<u> </u>		
Color	Visual	Yellow Fluo
Density at 20°C (68°F)	ASTM D4052	1.056
рН	ASTM D1287	8.5
Freezing point	NFT 78102	-25.0 °C
Freezing protection		-25.0 °C / -13.0 °F
Boiling point	NFR 15602-4	107°C / 225°F