AUTO COOL TYPE E - 5110

Ready to use RENAULT & PSA cooling liquid - Anti-corrosion
Anti-freezing protection -37°C / -35°F
P-OAT - Lobrid Tech
Nitrite free / Amine free / Borate / Silicate free

TYPE OF USE

MOTUL AUTO COOL TYPE E - 5110 is a ready-to-use coolant specially formulated with monoethylene glycol, using a mixed P-OAT, Phosphate Organic and Inorganic technology, known as Lobrid additive, to specifically meet both the PSA B71 5110 standard required by the STELLANTIS brands - PSA Group: PEUGEOT, CITROËN, DS; and the RENAULT TYPE E standard required by the RENAULT Group brands: RENAULT, DACIA, ALPINE, MITSUBISHI, and NISSAN. This Renault Type E standard also covers the former Renault TYPE D standard and is therefore fully backward compatible.
Compatible with ethylene glycol-based coolants.

PERFORMANCES

Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.
Specifically meets the requirements of PSA B71 5110 and PSA B71 1111 standards required by the STELLANTIS brands - PSA Group (Peugeot, Citroën, and DS), and also the RENAULT TYPE E standard (covering TYPE D) required by the RENAULT Group brands.
This premium P-OAT coolant technology ensures maximum and long-lasting protection against freezing, corrosion, and scale buildup in cooling systems, as well as for ferrous and non-ferrous metals and aluminum, even at high temperatures.
Hybrid technology promotes heat exchange and enables efficient engine cooling while delaying the boiling point. Enhanced heat exchange allows for efficient and long-lasting engine cooling.
Compatible with seals, hoses, and plastic components.

RECOMMENDATIONS

Ready to use, do not dilute, do not add any water.
Drain intervals: Refer to the manufacturers' recommendation.
This product should not be used to protect drinking water systems against freezing.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

AUTO COOL TYPE E - 5110

Ready to use RENAULT & PSA cooling liquid - Anti-corrosion
Anti-freezing protection -37°C / -35°F
P-OAT - Lobrid Tech
Nitrite free / Amine free / Borate / Silicate free

PROPERTIES

Color	Visual	Dark blue green
Density at 20°C (68°F)	ASTM D5931	1.071
pH	ASTM D1287	8.0
Freezing protection		-37.0 °C / -35.0 °F
Boiling point	ASTM D1120	113.0 °C / 235.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

AUTO COOL TYPE E - 5110

Ready to use RENAULT & PSA cooling liquid - Anti-corrosion
Anti-freezing protection -37°C / -35°F
P-OAT - Lobrid Tech
Nitrite free / Amine free / Borate / Silicate free

OEM PERFORMANCES	
CITROËN	PSA B71 1111, PSA B71 5110
DS (CAPSA)	PSA B71 1111, PSA B71 5110
NISSAN	RNES-B-00014 v2.1 / TYPE E
PEUGEOT	PSA B71 1111, PSA B71 5110
RENAULT	41-01-001 –V / TYPE E
PRODUCTS	
PSA Groupe	PSA B71 1111, PSA B71 5110

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com