



MOTULTECH BAR SY 46

High Performance Compressor Oil

DESCRIPTION

BAR SY 46 is a fully-synthetic high performance oil with a high Viscosity Index for rotating and reciprocating air compressors for extended oil change intervals.

APPLICATIONS

BAR SY 46 is particularly effective for compressors operating under extreme climatic conditions, harsh environments and other severe operating environments.

BAR SY 46 can be use on the large range of temperatures, thanks to their high viscosity index. Their thermal and oxidation stability provide increased drain oil interval for reduced maintenance costs. Their very low volatility allows the reduction of lubricant consumption.

BAR SY 46 meets the following requirements:

- DIN 51506 - VCL & VDL

Recommended drain oil interval: 8,000 hours.

ADVANTAGES

- Excellent wear and corrosion protection.
- Very long drain intervals for reduced compressor maintenance.
- Reduces varnish and lacquer deposits.
- High viscosity index.
- Very low volatility for lower oil consumption.
- High oxidation resistance.
- Excellent separation from air and water.

**TECHNICAL INFORMATION**

TECHNICAL CHARACTERISTICS	UNITS	METHOD	BAR SY 46
Aspect	-		Clear
Color	-	ASTM D1500	0,5
Density	-	ISO 12185	0,858
Viscosity at 40°C	cST	ASTM D445	45.9
Viscosity at 100°C	cST	ASTM D445	7.5
Viscosity index	-	ASTM D2270	128.0
Flash point	°C	ASTM D92	238.0
Pour point	°C	ASTM D97	-36.0
Copper corrosion	-	ISO 2160	1b
4 Ball test - Wear scar	mm	ISO 20623	1,59
Foaming Seq I, II, III	mL/mL	NF T 60 129	0/0-0/0-0/0

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

Information disclosed in this technical data sheet is based on MOTUL's experience and know-how in the development and manufacture of lubricants and other chemical products according to the current state of knowledge.

Any chemical product must be used in the intended application and in accordance with the recommendations provided in its safety data sheet freely consultable via the site <https://www.quickfds.com/fr/>. The performance of our products may be influenced by a series of factors, including conditions of use, application methods, operational environment, pretreatment of components, possible external contamination, etc ... For these reasons, universal recommendation of our products is impossible. The information in the technical data sheet represents general, non-binding guidelines and is given for guidance only. No express or implied warranty is given regarding the properties of the product or its suitability for a given application.

Therefore, we recommend consulting an application engineer to discuss application conditions and product performance criteria before use. It is the user's responsibility to test the functional suitability of the product and to use it under appropriate safety conditions. Our products are subject to continuous improvement with the aim of improving performance or bringing them into compliance with any new and possible regulations concerning them. We reserve the right to change our product lines, our products and their manufacturing processes and any provisions of our publications at any time without notice. This technical sheet cancels and replaces all previous editions.

We expressly draw the attention of any user to the fact that our product has not been designed and tested for use in the field of aeronautics as an "onboard" product or in the field of nuclear power production. Any use that may be made of the product in one of the aforementioned sectors will be under the exclusive responsibility of the user. Any reproduction, whatever its form, requires the prior written consent of MOTUL. All rights reserved.