



## MOTULTECH CADREX EV 1400

VANISHING NEAT OIL

### DESCRIPTION

**CADREX EV 1400** is a chlorine and Sulphur free vanishing fluid, specifically designed for the forming and cutting of steel, stainless steel, aluminium and copper alloys.

**CADREX EV 1400** complies with US FDA status and meets the requirements of the food industry.

### APPLICATIONS

**CADREX EV 1400** is a range of vanishing lubricants that are mainly used for the forming and cutting of steel, aluminum and copper alloys.

**CADREX EV 1400** is best suited for non-severe operations on sheets with a thickness up to 2mm. Can be used by low pressure spraying, roller, impregnation or by dipping.

### ADVANTAGES

- Low smell.
- Good wettability.
- Fast evaporation.
- Leaves no residues and ther-modegradable.
- Application : low pressure spraying, roller, impregnation by dipping.

### TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	CADREX EV 1400
Aspect	-		Liquid
Vapour Pressure	kPa		0.01 at 20°C / 0.03 at 37.8°C

These characteristics are given only for information and can be updated over time.

### SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



#### Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on [www.motul.com](http://www.motul.com).

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.