



MOTULTECH CADREX EV 1800

Vanishing Neat Oil

DESCRIPTION

CADREX EV 1800 is an evanescent odorless chlorine-free and strongly additivated fluid dedicated to deformation and cut of medium-hard and hard steels, high-alloy steels and very thick stainless steels.

APPLICATIONS

CADREX EV 1800 has been especially developed for metal sheets with thickness from 3 to 10mm (HLE, XES, galvanized, stainless steel):

- Forming and stamping
- Stamping on high thickness
- Blanking

ADVANTAGES

- Fast evaporation.
- Dry content without wax.
- Low surface tension.
- Uses: low pressure pulverisation, spraying, immersion impregnation, drop-by-drop.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	CADREX EV 1800
Aspect	-		Clear
Dry Content	%	NFT 30 084	20.0

These characteristics are given only for information and can be updated over time.

HEALTH AND SAFETY

- Exempt d'additif organochloré et de libérateur de formaldéhyde
- Bon comportement dermatologique pour un meilleur confort des utilisateurs
- Stockage hors gel, dans un endroit sec

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.