



## MOTULTECH CENTER OIL FZ-8209E

Deformation

### DESCRIPTION

**CENTER OIL FZ-8209E** is a non-chlorinated very high performance neat oil. Since special additives are being used, improvements in tool life such as punch and die can be expected in cold forging.

**CENTER OIL FZ-8209E** is a product dedicated for metalworking especially for forming applications.

**CENTER OIL FZ-8209E** provides excellent performance at the time of molding of plate material and can extend the tool life at time of burring or tapping.

**CENTER OIL FZ-8209E** is made for ferrous metals only.

### APPLICATIONS

**CENTER OIL FZ-8209E** is suitable for :

- Cold forging on steel, carbon steel, alloyed steel and stainless steel
- Drawing on steel, carbon steel, alloyed steel, stainless steel

### ADVANTAGES

- Free from organo-chlorinated additives.
- Extended tool life thanks to EP and lubricating properties.
- Better parts finishing.

### TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	CENTER OIL FZ-8209E
Aspect	-		Transparent
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

### INSTRUCTIONS

After skin contact, please wash with soapy water and please use protection cream.



## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

### Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on [www.motul.com](http://www.motul.com).

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.