



MOTUL CLASSIC 20W-50

**Petrol and Diesel Engine Oil
For Classic Cars and vehicles
Mineral Multigrade**

TYPE OF USE

Premium Mineral multigrade engine oil specially designed for classic engines built between 1950 and 1970. Lubricant for 4 stroke petrol or Diesel engines, naturally aspirated or turbocharged with carburettor or injection, SAE 20W-50 formula meets 1950-1970 standards (API SF/CC) and combines MOTUL's current advanced technology, developed in motorsports, to deliver a complete performance package for your classic car.

PERFORMANCES

MOTUL CLASSIC PERFORMANCE 20W-50 is formulated with a unique combination of high-Zinc (ZDDP content above 1800 ppm) and Molybdenum (Moly) additives to provide the best performance for larger displacement engines, while still offering protection of critical engine components like high-lift cams and flat-tappets.

Medium detergent level compatible with elastomer gaskets. Offers excellent oil consumption control, good shear stability and better cold engine start-ups to prevent engine wear after long periods of storage. Multigrade engine oil suitable for year-round use (all seasons protection).

CLASSIC PERFORMANCE 20W-50 meets manufacturers' standards from that time while benefiting of the advanced technology of today's MOTUL lubricants.

The high viscosity grade at high temperature (SAE 50) is totally adapted to high mileage engines which tend to be heavy on oil consumption.

Caution: This oil is rated API SF. It is not suitable for use in most petrol-powered automotive engines built after 1988. Use in modern engines may not provide adequate protection against build-up of engine sludge, oxidation, or wear.

Leaves an oil film protection on engine moving parts during wintering periods.

RECOMMENDATIONS

Drain intervals: drain at least once a year and tune to your own use.

Can be mixed with synthetic or mineral oils.



MOTUL CLASSIC 20W-50

**Petrol and Diesel Engine Oil
For Classic Cars and vehicles
Mineral Multigrade**

PROPERTIES

Viscosity grade	SAE J 300	20W-50
Density at 20°C (68°F)		0.887
Viscosity at 40°C (104°F)	ASTM D445	155.5 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	17.8 mm²/s
Viscosity Index	ASTM D4741	126.0
Pour point	ASTM D97	-33.0 °C / -27.0 °F
TBN	ASTM D2896	8.8 mg KOH/g
Flash point	ASTM D92	236.0 °C / 457.0 °F



MOTUL CLASSIC 20W-50

**Petrol and Diesel Engine Oil
For Classic Cars and vehicles
Mineral Multigrade**

STANDARDS	
API	SF/CC

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

