



MOTULTECH DEMOLD SPRAY

Release Agent for Plastics

SYNTHETIC BASE

DESCRIPTION

DEMOLD SPRAY is a release agent for plastics. It allows any subsequent decorating process such as painting, screen printing, gluing or adhesive bonding.

APPLICATIONS

DEMOLD SPRAY is recommended for the following applications:

- Plastics and rubber industries: Demolding of plastics and rubbers, demolded plastic parts intended for post finishing treatments.
- Food industry: Mold anti-adhesion treatment, belt lubrication, treatment of guide rails and skin-pack cutting machines.
- Paper industry: Treatment of press plates and cutting machines.
- Printing industry: Treatment of cutting guillotines.
- Packaging industries: Treatment of belts, guide rails and blister-packaging tools.

ADVANTAGES

- High temperature stable, inflammable.
- Excellent anti-wear properties.
- Very good corrosion protection
- Compatible with any kind of metals, plastics and elastomers.

TECHNICAL INFORMATION

| TECHNICAL CHARACTERISTICS | UNITS | METHOD | DEMOLD SPRAY |
|---------------------------|-------|--------|--------------------|
| Aspect | - | | Liquid |
| Temperature range | - | | -40 °C to + 200 °C |

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.