



DOT 5.1 DE

**Long life 100% Synthetic Brake Fluid For hydraulic actuated brake and clutch systems
DOT 5.1 NON SILICONE BASE**

TYPE OF USE

For all types of hydraulically actuated brake and clutch systems requiring fluids meeting DOT 3, DOT 4, or DOT 5.1 specifications as per manufacturers' recommendations.

Fluidity specially designed for anti-locking brake systems (ABS) and other electronic stability programs (ESP, ASR,...)

PERFORMANCES

STANDARDS FMVSS 116 DOT 3 / 116 DOT 4 / 116 DOT 5.1 NON SILICONE BASE
SAE J1703 / J1704

Long life fluid:

MOTUL DOT 5.1 high wet boiling point (185°C / 365°F) is superior than the requirements of the standards DOT 3 (140°C mini / 284°F mini), DOT 4 (155°C mini / 311°F mini) and DOT 5.1 (180°C mini / 356°F mini), and therefore enables longer use of this product.

Indeed, DOT 3, DOT 4 or DOT 5.1 brake fluids have the property of absorbing moisture from the air, which reduces their boiling points and therefore braking safety.

The wet boiling point is measured after moistening the product with 3% water in order to be representative of the state of the fluid after 1 year of use.

Perfectly neutral with seals used in braking systems. Anti-corrosion.

Specially designed for anti-locking brake systems (ABS):

The viscosity at cold temperature (820 mm²/s at -40°C / -40°F) of MOTUL DOT 5.1 is lower than DOT 4 (up to 1800 mm²/s) and DOT 3 (up to 1500 mm²/s) brake fluid specifications and allows easier fluid circulation and flow through the micro-valves of anti-locking systems for better response of ABS and other electronic stability programs (ESP, ASR,...) requiring quick brake systems actuation.



DOT 5.1 DE

Long life 100% Synthetic Brake Fluid For hydraulic actuated brake and clutch systems
DOT 5.1 NON SILICONE BASE

RECOMMENDATIONS

Oil changes: 12 to 24 months according to the manufacturers' recommendations. For safety advice, draining once a year is recommended.

Mixable with DOT 3, DOT 4 and DOT 5.1 NON SILICONE BASE products.

Do not mix with silicone (DOT 5 silicone base) or mineral base fluids (LHM).

Store brake fluid in its original container, tightly closed to avoid absorption of moisture.

Aggressive chemical product if contact with hands, paint or varnish.

If skin contact, rinse thoroughly with water.

PROPERTIES

Couleur	Jaune
Viscosité à 100°C (212°F)	2.1 mm²/s
Viscosité à -40°C (-40°F)	820.0 mm²/s
Point d'ébullition sec	272.0 °C / 522.0 °F
Point d'ébullition humide	185.0 °C / 365.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 -