



MOTUL DRIVE SUPRA 80W

**Heavy-Duty Transmission and Differential lubricant
Mineral**

TYPE OF USE

DRIVE SUPRA 80W is an Extreme Pressure (EP) lubricant specifically formulated for use in truck gearboxes, including those manufactured by Mercedes-Benz, MAN, and ZF (Ecolite, Ecomid, Ecosplit, and AS-Tronic 1 and 2 without Intarder).

It is suitable for all gearboxes and gearbox/differential units without a limited slip system that operate under moderate load and speed conditions, as well as for transfer gearboxes, mechanical transmissions without hypoid gears, and reduction gears operating under moderate to severe load and speed.

PERFORMANCES

STANDARDS	API GL-4
APPROVALS	BOSCH TE-ML 08 ZF TE-ML 24A ZF TE-ML 17A
PERFORMANCES	MAN 341 Type E2

DRIVE SUPRA 80W provides effective anti-wear protection and offers excellent lubricating properties that help reduce friction. It is compatible with all types of seals and contains additives that protect against corrosion and prevent foam formation.

RECOMMENDATIONS

Can be mixed with synthetic or mineral oils.

Oil changes should be performed according to the manufacturer's recommendations. Consult your vehicle's owner's manual or contact a dealer for specific guidelines, as they vary.



MOTUL DRIVE SUPRA 80W

**Heavy-Duty Transmission and Differential lubricant
Mineral**

We also recommend the use of an oil monitoring program to optimize oil change intervals and maximize equipment protection.

PROPERTIES

Color	ASTM D1500	Amber
Viscosity grade	SAE J 300	80W
Density at 20°C (68°F)	ASTM D1298	0.886
Viscosity at 40°C (104°F)	ASTM D445	105.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	8.5 mm ² /s
Viscosity Index	ASTM D2270	105
Pour point	ASTM D97	-30.0 °C / -22.0 °F
Flash point	ASTM D92	219 °C / 426 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.