



MOTUL DRIVE SUPRA 85W-140

**Heavy-Duty Transmission and Differential lubricant
Mineral**

TYPE OF USE

DRIVE SUPRA 85W-140 is an extreme-pressure (EP) lubricant designed for use in all types of mechanical transmissions, reduction gears, and hypoid differentials without limited-slip systems. It is particularly suited for applications operating under shock loads, heavy loads at low rotational speeds, or moderate loads at high rotational speeds.

DRIVE SUPRA 85W-140 is particularly recommended when a standard xxW-90 lubricant specified by the gearbox manufacturer is insufficient to withstand very heavy loads, shock conditions, or high temperatures.

PERFORMANCES

DRIVE SUPRA 85W-140 provides effective protection against wear. It maintains SAE 140 viscosity grade after 20 hours of shear testing in accordance with the SAE J306 standard (KRL test), ensuring consistent performance under mechanical stress.

The oil's exceptionally high lubricating power helps reduce friction and wear. Its high viscosity at elevated temperatures enhances oil film resistance under extreme operating conditions, including heavy loads, shock impacts, and high thermal environments. The formulation ensures excellent oil film stability at high temperatures, along with reliable anti-corrosion and anti-foam performance.

RECOMMENDATIONS

Can be mixed with synthetic or mineral oils.

Oil changes should be performed according to the manufacturer's recommendations. Consult your vehicle's owner's manual or contact a dealer for specific guidelines, as they vary.

We also recommend the use of an oil monitoring program to optimize oil change intervals and maximize equipment protection.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

09/25



MOTUL DRIVE SUPRA 85W-140

**Heavy-Duty Transmission and Differential lubricant
Mineral**

PROPERTIES

Color	ASTM D1500	Amber
Viscosity grade	SAE J 306	85W-140
Density at 20°C (68°F)	ASTM D1298	0.893
Viscosity at 40°C (104°F)	ASTM D445	339.0 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	25.1 mm²/s
Viscosity Index	ASTM D2270	96
Pour point	ASTM D97	-21.0 °C / -6.0 °F
Flash point	ASTM D92	200 °C / 392 °F



MOTUL DRIVE SUPRA 85W-140

**Heavy-Duty Transmission and Differential lubricant
Mineral**

STANDARDS	
API	GL-4, GL-5
MIL-PRF	2105 D
OEM PERFORMANCES	
VOLVO	97310
PRODUCTS	
ZF	TE-ML 07A, TE-ML 08

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

