



MOTUL DRIVE SUPRA 90

**Heavy-Duty Transmission and Differential lubricant
Mineral**

TYPE OF USE

DRIVE SUPRA 90 is a mineral gear oil engineered to deliver reliable lubrication and protection for a wide range of heavy-duty automotive and industrial applications.

Formulated with premium base oils and advanced additive technology, it is designed to provide excellent Extreme Pressure (EP) performance, superior wear protection, and consistent operation under severe load and temperature conditions.

PERFORMANCES

DRIVE SUPRA 90 is particularly well-suited for use in manual transmissions, axles, and final drives where SAE 90 viscosity and API GL-5 performance levels are required.

It offers outstanding resistance to oxidation and thermal degradation, ensures smooth gear operation, and helps extend the service life of critical drivetrain components.

RECOMMENDATIONS

Can be mixed with synthetic or mineral oils.

Oil changes should be performed according to the manufacturer's recommendations. Consult your vehicle's owner's manual or contact a dealer for specific guidelines, as they vary.

We also recommend the use of an oil monitoring program to optimize oil change intervals and maximize equipment protection.

PROPERTIES

Color	ASTM D1500	Amber
Viscosity grade	SAE J 306	90
Density at 20°C (68°F)	ASTM D1298	0.895

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

07/26



MOTUL DRIVE SUPRA 90

**Heavy-Duty Transmission and Differential lubricant
Mineral**

Viscosity at 40°C (104°F)	ASTM D445	190.0 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	17.0 mm²/s
Viscosity Index	ASTM D2270	95
Pour point	ASTM D97	-15.0 °C / -5.0 °F
Flash point	ASTM D92	214 °C / 417 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



MOTUL DRIVE SUPRA 90

**Heavy-Duty Transmission and Differential lubricant
Mineral**

STANDARDS	
API	GL-5
DAIMLER	DTFR 12B100 (former MB 235.0)
ZF	TE-ML 16C, TE-ML 17B, TE-ML 19B, TE-ML 21A
OEM PERFORMANCES	
MAN	342 Type M1
VOITH	132.00374400 (previously 3.325.339)
VOLVO	97310
VW	TL 727
ZF	TE-ML 08

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.