



MOTUL DRIVE ULTIMA 75W-90

Heavy Duty Manual Transmission Fluid
100% synthetic

TYPE OF USE

DRIVE ULTIMA 75W-90 is a fully synthetic gear lubricant engineered for universal use in manual gearboxes, auxiliary drives, and differentials across a wide range of applications, including commercial vehicles, agricultural machinery, and construction equipment.

This lubricant is particularly suitable for commercial vehicles requiring ZF, Scania, or MAN approvals for manual transmissions. It is designed for both factory and service fill in commercial vehicle manual gearboxes, offering wide synchronizer compatibility and superior cleanliness.

PERFORMANCES

STANDARDS	API GL-4
APPROVALS	MAN 341 Type GA2 SCANIA STO 2:0 G
PERFORMANCES	MAN 341 Type E2 MAN 341 Type Z2 ZF TE-ML 02B ZF TE-ML 06L ZF TE-ML 08 ZF TE-ML 17A ZF TE-ML 24A

Formulated with advanced synthetic base oils and state-of-the-art additive technology, **DRIVE ULTIMA 75W-90** offers multiple benefits for heavy-duty drivetrains:

- Exceptional load-carrying capability, ensuring reliable operation under extreme pressures and shock loading.
- Excellent protection against thermal degradation and oxidation, reducing wear and minimizing corrosion.
- Improved shear stability for consistent performance over extended service intervals.
- Smooth gear shifting even at low temperatures for enhanced drivability.
- Outstanding gear protection that extends component life under heavy-duty operating conditions.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

09/25



MOTUL DRIVE ULTIMA 75W-90

Heavy Duty Manual Transmission Fluid
100% synthetic

RECOMMENDATIONS

Can be mixed with synthetic or mineral oils.

Oil changes should be performed according to the manufacturer's recommendations. Consult your vehicle's owner's manual or contact a dealer for specific guidelines, as they vary.

We also recommend the use of an oil monitoring program to optimize oil change intervals and maximize equipment protection.

PROPERTIES

Color	ASTM D1500	Amber
Viscosity grade	SAE J 300	75W-90
Density at 20°C (68°F)	ASTM D1298	0.852
Viscosity at 40°C (104°F)	ASTM D445	104.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	16.7 mm ² /s
Viscosity Index	ASTM D2270	175
Pour point	ASTM D97	-45.0 °C / -49.0 °F
Flash point	ASTM D97	-45 °C / -49 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com