



MOTUL DRIVE ULTIMA ATF

**Automatic Transmission Fluid
Heavy Duty, Bus & Coach
100% synthetic**

TYPE OF USE

DRIVE ULTIMA ATF is a fully synthetic lubricant specifically formulated for use in most modern heavy-duty automatic truck, bus, and coach transmissions, including manual mode, sequential mode, and electronically controlled systems, with or without a slip lockup clutch. This oil delivers robust protection for modern automatic transmissions, which are increasingly compact, heavily loaded, and feature a high number of speeds.

DRIVE ULTIMA ATF provides extended drain intervals even under the most severe operating conditions and is ideally suited for frequent stop-and-go driving. This product is particularly recommended for use in ZF and Voith automatic transmissions.

PERFORMANCES

APPROVALS

DAIMLER DTFR 13C160 (former MB 236.81)
DAIMLER DTFR 13C170 (former MB 236.9)
MAN 339 Type V3
MAN 339 Type Z11
MAN 339 Type Z12
VOITH 150.014524.xx
VOLVO 97340 AT100
VOLVO 97341 AT101
ZF TE-ML 14C (for ZF Ecomat and EcoLife automatic transmissions)
ZF TE-ML 20C (for ZF EcoLife automatic transmissions)
ZF TE-ML 25C (for EcoLife Offroad automatic transmissions)
ZF TE-ML 16M
ZF TE-ML 16S
ZF TE-ML 04D

PERFORMANCES

ZF TE-ML 14A
ZF TE-ML 14B
ZF TE-ML 16L
ZF TE-ML 16R

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

09/25

**Automatic Transmission Fluid
Heavy Duty, Bus & Coach
100% synthetic**

ZF TE-ML 20B
ZF TE-ML 25B
MAN 339 Type V1
MAN 339 Type V2
MAN 339 Type Z1
MAN 339 Type Z2
MAN 339 Type Z3
VOITH H55.6335.xx; Svc Bltn #013
VOITH H55.6336.xx; Svc Bltn #118

DRIVE ULTIMA ATF is designed to deliver superior performance compared to conventional ATF products. It combines advanced synthetic base oils with a specialized additive package to ensure reliable operation under demanding conditions.

- Provides extended drain intervals through excellent oxidation resistance and outstanding shear stability, even at high operating temperatures.
- Delivers reliable anti-shudder performance, preventing vibrations at the engine flywheel for smoother operation.
- Enhances transmission responsiveness, enabling smooth shifting with reduced time lag.
- Improves gearbox performance at low temperatures for easier operation in cold conditions.
- Offers complete protection with anti-wear, anti-corrosion, and anti-foam properties, ensuring long-lasting transmission life and dependable performance.

RECOMMENDATIONS

Can be mixed with synthetic or mineral oils.

Oil changes should be performed according to the manufacturer's recommendations. Consult your vehicle's owner's manual or contact a dealer for specific guidelines, as they vary.

We also recommend the use of an oil monitoring program to optimize oil change intervals and maximize equipment protection.



MOTUL DRIVE ULTIMA ATF

**Automatic Transmission Fluid
Heavy Duty, Bus & Coach
100% synthetic**

PROPERTIES

Color	ASTM D1500	Amber
Density at 20°C (68°F)	ASTM D1298	0.838
Viscosity at 40°C (104°F)	ASTM D445	38.1 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	7.3 mm²/s
Viscosity Index	ASTM D2270	169
Drop point	ASTM D97	-42 °C / -44 °F
Flash point	ASTM D92	240 °C / 464 °F