

**Lubricant for HONDA motorbikes**  
**100% Synthetic**

**TYPE OF USE**

100% Synthetic high performance lubricant specially designed for HONDA motorbikes : street and road bikes, trails, off-road bikes, enduro,..., fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch; engines requiring a low viscosity grade, engines meeting Euro 2, 3 or 4 emission regulation, fitted with exhaust gas after treatment systems : catalytic converters, air injection into exhaust pipe,...

Other uses : street bikes without catalytic converter, scooters, maxi-scooters,...

Must be use only when manufacturers recommend this type of lubricant. When in doubt, always refer to the owner's manual.

**PERFORMANCES**

STANDARDS                      API SJ  
    JASO MA under N°M033MOT082

PERFORMANCES                HONDA MOTORCYCLES JAPAN under N°EU MOT 2009-00127

High performance engine oil developed in Japan with HONDA R&D engineers in order to meet the most stringent requirements of HONDA motorbikes.

100% Synthetic lubricant, result of the research and development between HONDA and MOTUL:

- Viscosity grade 30 at high temperature with dedicated technology, for improved fuel consumption of HONDA motorbikes and therefore CO<sub>2</sub> emission reduction. Provides oil consumption reduction.
- Low Phosphorus and Sulfur content for better operating conditions and duration of catalytic converters required to meet the latest emission regulations.
- Viscosity grade 10W at cold temperature for better engine wear protection during cold start and optimal anti-wear protection to ensure gears life time.
- Increase oil film shear resistance at high temperature for better gearbox protection and smoother gearshift.
- Specific additivation for perfect metallic material compatibility with HONDA gearboxes and wet clutches design to insure optimal protection.
- JASO MA approved to guarantee a perfect lock up of wet clutch.



## E-TEC LUB 10W-30

Lubricant for HONDA motorbikes  
100% Synthetic

### RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.  
Can be mixed with synthetic or mineral oils.

### PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.856
Viscosity at 40°C (104°F)	ASTM D445	65.6 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	10.1 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	139.0
Pour point	ASTM D97	-30.0 °C / -22.0 °F
Flash point	ASTM D92	240.0 °C / 464.0 °F
TBN	ASTM D2896	8.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com