

**FORK OIL EXPERT HEAVY 20W**

**Fluido hidráulico para todo tipo de Horquillas telescópicas**  
**Hydraulic Fluids for any type of telescopic forks**  
**Technosynthese®**

**TYPE OF USE**

Specially designed for any type of fork, upside-down ("USD") forks or conventional ("right-side-up») forks.

**PERFORMANCES**

Specific Technosynthese® formulation that contains exclusive anti-friction additive specially developed by MOTUL to create easier sliding and to avoid drag in the fork.

Stable absorption trough extended range of temperature thanks to the use of synthetic base stocks.

Seals protection: excellent lubricant / elastomer compatibility.

Anti-wear, anti-corrosion, anti-foaming.

**RECOMMENDATIONS**

MOTUL Fork Oil Expert can be mixed to obtain the required absorption effect. Use the exact quantity recommended by the fork manufacturer.

**PROPERTIES**

Density at 20°C (68°F)	ASTM D1298	0.874
Viscosity at 40°C (104°F)	ASTM D445	81.1 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	10.1 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	103.0
Flash point	ASTM D92	230.0 °C / 446.0 °F
Pour point	ASTM D97	-27.0 °C / -17.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com