



MOTUL FORK OIL FACTORY LINE LIGHT/ MEDIUM 7.5W

High Performance Hydraulic Fluid for any telescopic fork
100% Synthetic
LIGHT/MEDIUM

TYPE OF USE

Hydraulic fluid for racing applications.
Specially formulated for SHOWA, KAYABA, OHLINS, WP forks, and any type of upside/down or conventional telescopic fork.

PERFORMANCES

Reduced internal friction, specially fork tubes and seals thanks to the exclusive anti-friction additive designed and developed by MOTUL.
Outstanding suspension performance as soon as riding and maintained performance in time.
High performance anti-foam avoiding air transfer to the air chamber to maintain suspension performance.
Anti-wear and extreme pressure properties. Anti-corrosion. Seals protection.

RECOMMENDATIONS

MOTUL Fork Oil Factory Line can be mixed to obtain the required absorption effect.
Use the exact quantity recommended by the fork manufacturer.

PROPERTIES

Viscosity grade		7.5W
Density at 20°C (68°F)	ASTM D1298	0.838
Viscosity at 40°C (104°F)	ASTM D445	24.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	4.9 mm ² /s
Viscosity Index	ASTM D2270	131.0
Pour point	ASTM D97	-45.0 °C / -49.0 °F
Flash point	ASTM D92	208.0 °C / 406.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com