

FUEL SYSTEM CLEAN AUTO

Fuel system cleaner Additive to add to gasoline For car engine with carburetors or injection

TYPE OF USE

MOTUL FUEL SYSTEM CLEAN is designed to be used in all types of gasoline engine with injection or carburetors, naturally aspirated or turbocharged with or without catalytic converter, using all kind of gasoline. MOTUL FUEL SYSTEM CLEAN effectively cleans dirtying and clogging which appear in the whole fuel system:

- · condensation in the fuel system
- · gumming in the carburetor
- · injector nozzle fouling
- · dirtying of combustion chambers and inlet valves

MOTUL FUEL SYSTEM CLEAN provides a perfect lubrication during cleaning process and prevents removed micro-particles from depositing.

PERFORMANCES

A clean fuel system is a necessary condition for an effective engine running. MOTUL FUEL SYSTEM CLEAN allows to:

- clean the carburetors or the injectors (for a better atomization)
- prevent the formation of deposits and varnishes on inlet valves and in combustion chambers
- · disperse condensation water in order to avoid any fuel system oxidation

A regular use will provide:

- · optimum engine performances
- · fuel savings
- · increased lifetime of fuel system and catalytic converter
- · a reduction of exhaust pollutants emissions

RECOMMENDATIONS

Directly pour one can of FUEL SYSTEM CLEAN in the tank before refueling, regularly, depending on the use (shorten intervals in urban use). The fuel system will be then completely cleaned, from the tank to the combustion chamber.

A can of FUEL SYSTEM CLEAN is sufficient for tank capacity up to 60 liters. In case of bigger tank capacity, the recom-

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



FUEL SYSTEM CLEAN AUTO

Fuel system cleaner Additive to add to gasoline For car engine with carburetors or injection

mended mixing ratio is 0.50% (200:1). Do not exceed the recommended proportion. If necessary, proceed to 2 successive treatments.

Curative treatment: use the product pure by plugging on the fuel system with the adaptation kit.

SECURITY

Refer to the MSDS sheet and the information mentioned on the product label.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	NFT 60.101	0.772