



MOTUL GARDEN 2T

2 Stroke Engine Oil for Motorised Garden Tools
Technosynthese®

TYPE OF USE

Specially formulated for 2 Stroke engine garden tools.

Motor cultivator, chain saw, lawn mower, ground clearing machine...

Recommended for engines working under severe conditions or at high engine speeds.

Suitable with leaded or unleaded petrol.

PERFORMANCES

Pre-diluted lubricant which mixes instantaneously with petrol and remains stable.

Reinforced anti-rust and anti-corrosion properties.

Reduces deposits in exhaust pipes and on pistons.

Prevents spark plug from fouling.

RECOMMENDATIONS

Premix ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)		0.880
Viscosity at 40°C (104°F)	ASTM D445	79.2 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	10.0 mm²/s
Viscosity Index	ASTM D2270	107.0
Pour point	ASTM D97	-15.0 °C / 5.0 °F
Flash point	ASTM D92	178.0 °C / 352.4 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com



MOTUL GARDEN 2T

2 Stroke Engine Oil for Motorised Garden Tools
Technosynthese®

STANDARDS	
API	TC

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com