



MOTUL GARDEN 15W-40 4T

4 Stroke Engine Oil for Motorized Garden Tools
Petrol and diesel Engine
SAE 15W-40
Mineral

TYPE OF USE

Specially formulated for motorized garden tools and small farming equipment.

All petrol and Diesel 4 Stroke engines naturally aspirated or turbocharged.

Lawn mowers, motor mowers, ride on mowers, tillers, light tractors,...

Suitable for all types of fuel: leaded and unleaded petrol, Diesel fuel, Ethanol, biofuels.

All types of 4 stroke engines with or without catalytic converter.

PERFORMANCES

Ensures the engine cleanliness.

Protection during wintering.

Dispersant and detergent properties.

Good cold starting, perfectly stable in a hot engine.

Anti-oxidation, Anti-wear properties.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

MOTUL GARDEN 4T SAE 15W-40 can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	15W-40
Density at 20°C (68°F)		0.877
Viscosity at 40°C (104°F)	ASTM D445	99.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	13.4 mm ² /s
Viscosity Index	ASTM D2270	134.0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com



MOTUL GARDEN 15W-40 4T

4 Stroke Engine Oil for Motorized Garden Tools
Petrol and diesel Engine
SAE 15W-40
Mineral

Pour point	ASTM D97	-33.0 °C / -27.4 °F
TBN	ASTM D2896	7.8 mg KOH/g
Flash point	ASTM D92	234.0 °C / 453.2 °F



MOTUL GARDEN 15W-40 4T

4 Stroke Engine Oil for Motorized Garden Tools
Petrol and diesel Engine
SAE 15W-40
Mineral

STANDARDS	
API	SF/CD

