



GASMA X SAE 40

Industrial engine oil

TYPE OF USE

MOTUL GASMA X SAE 40 is a high performance state-of-the-art mineral engine oil dedicated to the latest generation of 4-stroke engines running with natural gas and requiring low ash oil.

MOTUL GASMA X SAE 40 high quality base oil and latest additive technology provides superior valve recession protection in order to reduce nitration phenomena. The additive system reduces sludge deposit and plug fouling leading to increased spark plug life enabling longer operating life and lowering maintenance costs.

PERFORMANCES

APPROVALS

MWM TCG

PERFORMANCES

CATERPILLAR 3516H

Bergen Engines B35:40V (natural gas)

WÄRTSILÄ Engine types 175SG, 220SG, 25SG, 28SG, 31SG, 34SG, 50SG, 20DF, 31DF, 32DF, 34DF, 46DF and 50DF with natural gas as main fuel

MOTUL GASMA X SAE 40 is a high performance natural gas engine oil for latest generation 4-stroke, spark-ignition stationary gas engines.

RECOMMENDATIONS

Drain interval: Refer to manufacturer's recommendations and adjust to your own use (engine type, service).

Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade

SAE J 300

SAE 40

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

09/25



GASMA X SAE 40

Industrial engine oil

Density at 20°C (68°F)	ASTM D1298	0.875
Viscosity at 40°C (104°F)	ASTM D445	121.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	13.8 mm ² /s
Viscosity Index	ASTM D2270	111.0
Pour point	ASTM D97	-0.4 °C / -33.0 °F
Sulfated Ash	ASTM D874	% weight 0.50
TBN	ASTM D2896	7.3 mg KOH/g
Flash point	ASTM D92	230.0 °C / 446.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.