

Industrial engine oil**TYPE OF USE**

MOTUL GASMA X SAE 40 is a high performance state-of-the-art mineral engine oil dedicated to the latest generation of 4-stroke engines running with natural gas and requiring low ash oil.

MOTUL GASMA X SAE 40 high quality base oil and latest additive technology provides superior valve recession protection in order to reduce nitration phenomena. The additive system reduces sludge deposit and plug fouling leading to increased spark plug life enabling longer operating life and lowering maintenance costs.

PERFORMANCES

MOTUL GASMA X SAE 40 is a high performance natural gas engine oil for latest generation 4-stroke, spark-ignition stationary gas engines.

RECOMMENDATIONS

Drain interval: Refer to manufacturer's recommendations and adjust to your own use (engine type, service).

Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	SAE 40
Density at 20°C (68°F)	ASTM D1298	0.875
Viscosity at 40°C (104°F)	ASTM D445	121.0 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	13.8 mm²/s
Viscosity Index	ASTM D2270	111.0
Pour point	ASTM D97	-18.0 °C / -0.4 °F
Sulfated Ash	ASTM D874	% weight 0.50
TBN	ASTM D2896	7.3 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



MOTUL GASMA X SAE 40

Industrial engine oil

Flash point

ASTM D92

230.0 °C / 446.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



MOTUL GASMA X SAE 40

Industrial engine oil

STANDARDS	
Bergen Engines	B35:40 (natural gas), B36:45 (natural gas), C26:33 (natural gas), K-type (natural gas)
CATERPILLAR	CG
Innio Jenbacher	Type 2 all versions, Type 3 all versions, Type 4, version B
MWM	TCG
OEM PERFORMANCES	
CATERPILLAR	SEBU6400
Innio Jenbacher	Type 4, version A, Type 6 all versions (incl J624)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.