



MOTUL GEAR MB 80W

Gear box lubricant
Gearbox lubricant
Extreme Pressure
Mineral

TYPE OF USE

GEAR MB 80W is a heavy duty Extreme Pressure gearbox lubricant.

PERFORMANCES

Sehr hohes Druckaufnahmevermögen garantiert eine optimale Getriebeschmierung auch bei hohen Temperaturen.
Senkt die Reibung und verhindert Verschleiß.
Vermeidet Korrosion und schäumt nicht.

RECOMMENDATIONS

Oil drain: refer to manufacturer's recommendations and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE J 300	80W
Density at 20°C (68°F)		0.883
Viscosity at 40°C (104°F)	ASTM D445	89.3 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	10.8 mm²/s
Viscosity Index	ASTM D2270	105.0
Pour point	ASTM D97	-30.0 °C / -22.0 °F
Flash point	ASTM D92	219.0 °C / 426.0 °F



MOTUL GEAR MB 80W

Gear box lubricant
Gearbox lubricant
Extreme Pressure
Mineral

STANDARDS	
API	GL-4
OEM PERFORMANCES	
MAN	341 Typ E1, 341 Typ Z1, 341 Typ Z2
MERCEDES-BENZ	MB-Approval 235.1
ZF	TE-ML 17A under N° ZF000395
PRODUCTS	
ZF	TE-ML 17A under N° ZF000395

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.