



## MOTUL GEAR MB 80W

Gear box lubricant

Mineral Base

### DESCRIPTION

**GEAR MB 80W** is a heavy duty Extreme Pressure gearbox lubricant.

### APPLICATIONS

Sehr hohes Druckaufnahmevermögen garantiert eine optimale Getriebschmierung auch bei hohen Temperaturen.

Senkt die Reibung und verhindert Verschleiß.  
Vermeidet Korrosion und schäumt nicht.

### ADVANTAGES

- Extreme Pressure lubricant for an efficient anti-wear protection.
- Very high lubricating properties to reduce friction.
- Suitable for any type of seal.
- Anti-corrosion, anti-foam.

### TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	GEAR MB 80W
Viscosity grade	-	SAE J 300	80W
Density at 20°C (68°F)	-		0.883
Viscosity at 40°C (104°F)	mm <sup>2</sup> /s	ASTM D445	89.3
Viscosity at 100°C (212°F)	mm <sup>2</sup> /s	ASTM D445	10.8
Viscosity Index	-	ASTM D2270	105.0
Pour point	°C	ASTM D97	-30.0 / -22.0
Flash point	°C	ASTM D92	219.0 / 426.0

These characteristics are given only for information and can be updated over time.

### SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



#### Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on [www.motul.com](http://www.motul.com).

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.