

**GEAR OIL 90**

**Non EP - Extreme Pressure lubricant  
Mechanical transmissions lightly loaded**

**TYPE OF USE**

All mechanical transmission, manual gearboxes and differentials operating under mild loads and low revolution speed and moderate temperatures designed to use a straight mineral oil.

Recommended for transmissions or manual gearboxes of some trucks and buses VOLVO, TERBERG, SEDDON ATKINSON, LEYLAND TRUCK-SCAMMEL, LEYLAND DAF and FORD (GB).

**PERFORMANCES**

STANDARDS API GL-1

Straight pure mineral oil with :

- Rust inhibitor
- Oxidation inhibitor
- Foaming inhibitor

Does not contain any friction modifier.

**RECOMMENDATIONS**

Oil change: According to manufacturers' requirements and adjust according to your own use.

**PROPERTIES**

Viscosity grade	SAE J 300	90
Density at 20°C (68°F)	ASTM D1298	0.893
Viscosity at 40°C (104°F)	ASTM D445	150.0 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	15.0 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	100.0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com