

**Gearbox lubricant  
Synthetic Technology**

## TYPE OF USE

Recommended for manual transmissions that require a transmission oil of viscosity grade SAE 75W-80. Especially recommended for the mechanical transmissions of ALFA ROMEO, CITROËN, FIAT, FORD, PEUGEOT, RENAULT, MAZDA, NISSAN, SUZUKI, VOLKSWAGEN...etc.

All mechanical transmissions, synchronised or non-synchronised transmissions/axles or transfer cases without limited slip, operating with shock absorbers, under heavy loads and low speeds or moderate loads and high speeds and requiring an API GL-4 and SAE 75W-80 gear oil.

Also suitable for some "hard" or noisy transmissions.

Some manual transmissions are not designed to use this type of low viscosity gear oil. Always consult the vehicle's maintenance manual before use.

## PERFORMANCES

100% Synthetic gear lubricant formulated with "EP - Extreme Pressure" additives to protect against wear and reinforced with synthetic bases for better resistance at high temperature and longer lifetime.

Remains in viscosity grade 80 after the KRL 20 hours shear test required by SAE J306.

Very high lubricating power to reduce friction.

Viscosity grade 80 at high temperature to save fuel by reducing gearbox drag.

Great fluidity at low temperature which allows very easy gear shifting when cold.

Very easy gear shift engagements.

Compatible with all types of seals and materials used in manual gearboxes.

Anti-corrosion, Anti-foam.

## RECOMMENDATIONS

Oil change: As recommended by the manufacturers and to be adapted according to your own use.

Before use, always consult the vehicle maintenance owner's manual.



## MOTUL GEAR POWER 75W-80

**Gearbox lubricant  
Synthetic Technology**

### PROPERTIES

Viscosity grade	SAE J 306	75W-80
Density at 20°C (68°F)	ASTM D1298	0.854
	ASTM D445	69.4 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)	ASTM D445	10.5 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D97	-51.0 °C / -60.0 °F
Pour point		
Flash point	ASTM D92	234.0 °C / 453.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



## MOTUL GEAR POWER 75W-80

**Gearbox lubricant  
Synthetic Technology**

STANDARDS	
API	GL-4
OEM PERFORMANCES	
AUDI	G 009 317
BMW	MTF 94, MTF-LT-2
CITROËN	PSA B71 2330
DS (CAPSA)	PSA B71 2330
FIAT	9.55550-MZ6
GENERAL MOTORS	GM 1940764, GM 1940768
HONDA	MTF, MTF 94, MTF II, MTF III
INFINITI	MT-XZ, MT-XZ TL (JR Type)
LAND ROVER	MTF 94
MINI	MTF 94, MTF-LT-2
NISSAN	MT-XZ, MT-XZ TL (JR Type)
PEUGEOT	PSA B71 2330
RENAULT	Tranself NFJ, Tranself NFP, Tranself TRJ, Tranself TRT, Tranself TRZ
SEAT	G 009 317
SKODA	G 009 317
VOLVO	97308, 97309
VW	G 009 317
PRODUCTS	
ELF	Tranself NFJ, Tranself NFP, Tranself TRJ, Tranself TRT, Tranself TRZ
PSA Groupe	PSA B71 2330

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

06/24

