

**Gearbox and differential lubricant  
Synthetic Technology**

### TYPE OF USE

Recommended for the latest generation of manual transmissions that require a very fluid transmission oil of viscosity grade SAE 75W "FE - Fuel Economy".

Especially recommended for the latest mechanical transmissions from HONDA, RENAULT, NISSAN, SUZUKI, TOYOTA...  
All mechanical transmissions, synchronised or non-synchronised transmissions, gearboxes/axles, transfer cases or hypoid axles without limited slip, which operate with shift shocks, under high load and low speeds or moderate load and high speeds and require a transmission oil API GL-4 and SAE 75W.

Also suitable for some "hard" or noisy transmissions.

Some manual transmissions are not designed to use this type of low viscosity transmission fluid; always consult the vehicle's service manual before use.

### PERFORMANCES

#### STANDARDS **API GL-4**

PERFORMANCES **Refer to chart.**

100% Synthetic "FE - Fuel Economy" lubricant formulated with "EP - Extreme Pressure" additives to protect against wear and reinforced with synthetic bases for better resistance at high temperature and over time.

Remains in viscosity grade 75W after the KRL 20 hours shear test required by SAE J306.

Very high lubricating power to reduce friction.

Very good resistance of the oil film under heavy loads and high temperatures, reducing operating noise.

Very fluid at low temperature allowing very easy gear shifting when cold.

Very easy gear shift engagements for more energy saving.

Compatible with all types of seals and materials used in manual gearboxes.

Anti-corrosion, Anti-foam.



## MOTUL GEAR POWER FE 75W

**Gearbox and differential lubricant  
Synthetic Technology**

### RECOMMENDATIONS

Oil change: As recommended by the manufacturers and to be adapted according to your own use.  
Before use, always consult the vehicle maintenance owner's manual.

### PROPERTIES

Viscosity grade	SAE J 306	75W
Density at 20°C (68°F)	ASTM D1298	0.844
	ASTM D445	30.7 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)	ASTM D445	5.8 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D2270	134.0
Viscosity Index	ASTM D445	-45.0 °C / -49.0 °F
Pour point		
Flash point	ASTM D92	228.0 °C / 442.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

**Gearbox and differential lubricant  
Synthetic Technology**

STANDARDS	
API	GL-4
OEM PERFORMANCES	
AUDI	G 052 178, G 052 512, G 052 527, G 052 726, G 060 726, G 070 726
BMW	83 22 0 306 816, 83 22 0 397 244, MTF-LT-3
CITROËN	1618078480, JWS 2271, PSA B71 2310
DS (CAPSA)	1618078480, JWS 2271, PSA B71 2310
FIAT	9.55550-MZ2, Tutela Car Experia 75W
FORD	WSS-M2C200-D2, WSS-M2C200-D3, WSS-M2C200-E1
HONDA	MTF-III
INFINITI	LV MT-1
LEXUS	0888581001, JWS 2271, LV 75W MT, Transfer Gear Oil LF
MINI	83 22 0 306 816, 83 22 0 397 244, MTF-LT-3
NISSAN	LV MT-1
PEUGEOT	1618078480, JWS 2271, PSA B71 2310
PORSCHE	000 043 305 63, TF 0870
SEAT	G 052 178, G 052 512, G 052 527, G 052 726, G 060 726, G 070 726
SKODA	G 052 178, G 052 512, G 052 527, G 052 726, G 060 726, G 070 726
SUZUKI	99000-22B27-036
TOYOTA	0888581001, JWS 2271, LV 75W MT, Transfer Gear Oil LF
VOLVO	31280771
VW	G 052 178, G 052 512, G 052 527, G 052 726, G 060 726, G 070 726
ZOTYE	GB 13895-1992
PRODUCTS	
CASTROL	BOT 350 M1
ELF	Tranself NFX
MOPAR PARTS	68092630AA, 68092638AB
PETRONAS LUBRICANTS	Tutela Car Experia 75W
PSA Groupe	1618078480, JWS 2271, PSA B71 2310
SHELL	TF 0870

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

06/24

