



MOTUL GEAR POWER FE 75W

Gearbox and differential lubricant
100% Synthetic

TYPE OF USE

Recommended for latest generation of manual gearboxes requiring a very fluid "FE - Fuel Economy" SAE 75W viscosity grade transmission oil.

Particularly recommended for recent mechanical gearboxes from HONDA, RENAULT, NISSAN, SUZUKI, TOYOTA...

All mechanical transmissions, synchronized or non-synchronized gearboxes, gearbox/axle, transfer case or hypoid axles without limited slip operating with shocks, under heavy loads and low rotation speeds or moderate loads and high rotation speeds, requiring an API GL-4 and SAE 75W gear oil.

Also suitable for some "hard" or noisy gearboxes.

Some manual gearboxes are not designed to use this type of low-viscosity transmission lubricant, before use, always consult the vehicle maintenance manual.

PERFORMANCES

STANDARDS **API GL-4**

PERFORMANCES **Refer to chart.**

100% Synthetic "FE - Fuel Economy" lubricant formulated with "EP - Extreme Pressure" additives to protect against wear and reinforced with synthetic bases for better resistance at high temperature and over time.

Remains in viscosity grade 75W after the KRL 20 hours shear test required by SAE J306.

Very high lubricating power to reduce friction.

Very good resistance of the oil film under heavy loads and high temperatures, reducing operating noise.

Very fluid at low temperature allowing very easy gear shifting when cold.

Very easy gear shift engagements for more energy saving.

Compatible with all types of seals and materials used in manual gearboxes.

Anti-corrosion, Anti-foam.



MOTUL GEAR POWER FE 75W

Gearbox and differential lubricant
100% Synthetic

RECOMMENDATIONS

Oil change: As recommended by the manufacturers and to be adapted according to your own use.
Before use, always consult the vehicle maintenance owner's manual.

PROPERTIES

Viscosity grade	SAE J 306	75W
Density at 20°C (68°F)	ASTM D1298	0.844
Viscosity at 40°C (104°F)	ASTM D445	30.7 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	5.8 mm²/s
Viscosity Index	ASTM D2270	134.0
Pour point	ASTM D445	-45.0 °C / -49.0 °F
Flash point	ASTM D92	228.0 °C / 442.0 °F

Gearbox and differential lubricant
100% Synthetic

STANDARDS	
API	GL-4
OEM PERFORMANCES	
AUDI	G 052 178, G 052 512, G 052 527, G 052 726, G 060 726, G 070 726
BMW	83 22 0 306 816, 83 22 0 397 244, MTF-LT-3
CITROËN	1618078480, JWS 2271, PSA B71 2310
DS (CAPSA)	1618078480, JWS 2271, PSA B71 2310
FIAT	9.55550-MZ2, Tutela Car Experia 75W
FORD	WSS-M2C200-D2, WSS-M2C200-D3, WSS-M2C200-E1
HONDA	MTF-III
INFINITI	LV MT-1
LEXUS	0888581001, JWS 2271, LV 75W MT, Transfer Gear Oil LF
MINI	83 22 0 306 816, 83 22 0 397 244, MTF-LT-3
NISSAN	LV MT-1
PEUGEOT	1618078480, JWS 2271, PSA B71 2310
PORSCHE	000 043 305 63, TF 0870
SEAT	G 052 178, G 052 512, G 052 527, G 052 726, G 060 726, G 070 726
SKODA	G 052 178, G 052 512, G 052 527, G 052 726, G 060 726, G 070 726
SUZUKI	99000-22B27-036
TOYOTA	0888581001, JWS 2271, LV 75W MT, Transfer Gear Oil LF
VOLVO	31280771
VW	G 052 178, G 052 512, G 052 527, G 052 726, G 060 726, G 070 726
ZOTYE	GB 13895-1992
PRODUCTS	
CASTROL	BOT 350 M1
ELF	Tranself NFX
MOPAR PARTS	68092630AA, 68092638AB
PETRONAS LUBRICANTS	Tutela Car Experia 75W
PSA Groupe	1618078480, JWS 2271, PSA B71 2310
SHELL	TF 0870

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

