

MOTUL GEAR SYNT TDL 75W-90

Lubricant for heavily loaded transmissions and long drain service
Lubricant for heavily loaded transmissions and long drain service.
Synthetic Technology

TYPE OF USE

GEAR SYNT TDL 75W-90 is a lubricant for heavily loaded transmissions and long drain service.

PERFORMANCES

Sehr hohes Druckaufnahmevermögen garantiert eine optimale Getriebebeschmierung auch bei höheren Temperaturen.
 Vermindert die Getriebegeräusche
 Senkt die Reibung und verhindert Verschleiß
 Vermeidet Korrosion und schäumt nicht

RECOMMENDATIONS

Oil drains: refer to manufacturers' recommendations and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE J 300	75W-90
Density at 20°C (68°F)		0.866
	ASTM D445	105.0 mm ² /s
Viscosity at 40°C (104°F)		
	ASTM D445	15.7 mm ² /s
Viscosity at 100°C (212°F)		
	ASTM D2270	158.0
Viscosity Index		
	ASTM D97	-51.0 °C / -60.0 °F
Pour point		

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



MOTUL GEAR SYNT TDL 75W-90

Lubricant for heavily loaded transmissions and long drain service
Lubricant for heavily loaded transmissions and long drain service.
Synthetic Technology

Flash point

ASTM D92

202.0 °C / 381.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

06/24

MOTUL Deutschland GmbH - Butzweilerhofallee 3 - 50829 - Köln - +49(0)221/67003-0 - +49(0)221/67003-199 - info@motul.de - http://www.motul.com

Lubricant for heavily loaded transmissions and long drain service
Lubricant for heavily loaded transmissions and long drain service.
Synthetic Technology

STANDARDS	
API	GL-4, GL-5, MT-1
MIL-L	2105 D
MIL-PRF	-2105E
SAE	J2360
SCANIA	ST0 2:0 A (Transmission)
VOLVO	Transmission oil 97312
ZF	TE-ML 02B / 05A / 12L / 12N / 16F / 17B / 19C / 21A under n° ZF000825
OEM PERFORMANCES	
EATON	Europe Transmissions
MACK	GO-J
MAN	341 Types Z2 / E2, 342 Type M3
MERCEDES-BENZ	MB 235.8
MERITOR	076-N
PRODUCTS	
ARVIN	076-N
Eaton	Europe Transmissions

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

06/24

