

MOTUL HD-AGRI GREASE

Multipurpose Grease for Heavy Duty, Agriculture and Civil Engineering Machinery Multipurpose Grease for Heavy Duty, Agriculture and Civil Engineering Machinery Technosynthese® - NLGI 2 – Extreme Pressure

TYPE OF USE

HD-AGRI GREASE is a high performance multipurpose grease for Heavy Duty, Agriculture and Civil Engineering Machinery.

PERFORMANCES

HD-AGRI GREASE is a multipurpose grease specially formulated for applications requiring a good resistance to heavy loads and to water which are conditions encountered in Civil Engineering and Agriculture.

Greasing of roller bearings, articulations, bearings, cables...

Tractors, Combine (Harvester), Wine Machinery and all kind of Civil Engineering Machinery.

Operating temperature for long-term lubrication: from -30°C / -22°F to +140°C / +284°F.

PROPERTIES

T

Color	Visual	Green	
Base oil viscosity at 40°C	DIN 51562-01	800.0 mm²/s	
Base oil viscosity at 100°C	DIN 51562	65.0 mm²/s	
Consistency grade	DIN 51818	NLGI 2	
TIMKEN Test - Load	ASTM D2509	222.5 N	
Copper Strip Corrosion	ASTM D4048	1 / 120	
FAG FE-9 Test			
NLGI Grade	DIN 51818	NLGI 2	
Water washout	DIN 51807:1	1 / 90	
VKA welding load	DIN 51350	2,800.0 N	

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



MOTUL HD-AGRI GREASE

Multipurpose Grease for Heavy Duty, Agriculture and Civil Engineering Machinery Multipurpose Grease for Heavy Duty, Agriculture and Civil Engineering Machinery Technosynthese® - NLGI 2 – Extreme Pressure

STANDARDS		
DIN	51502 : KP 2 N-30	

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.