



HD-AGRI GREASE

МІНЕРАЛЬНА БАЗОВА ОЛИВА

DESCRIPTION

HD-AGRI GREASE - це високотехнологічне багатоцільове пластичне мастило для важкої, сільськогосподарської та будівельної техніки.

ПЕРЕВАГИ

- Відмінні результати в присутності води.
- Відмінна адгезивність.
- Відмінний антикорозійний та притизношувальний захист.
- Відмінний ресурс.
- Відмінні результати при високих навантаженнях

TECHNICAL CHARACTERISTICS

CHARACTERISTICS	METHOD	HD-AGRI GREASE
Color	Візуально	Зелений
Base oil viscosity at 40°C	DIN 51562-01	800,0 мм ² /с
В'язкість базової оливи при 100 ° C	DIN 51562	65,0 мм ² /с
Клас стійкості	DIN 51818	NLGI 2
Тест TIMKEN	ASTM D2509	222,5 N
Корозія мідної стрічки	ASTM D4048	1 / 120
Тест FAG FE-9		
NLGI Grade	DIN 51818	NLGI 2
Вимивання водою	DIN 51807:1	1 / 90
VKA welding load	DIN 51350	2 800,0 N



STANDARDS / APPROVALS / PERFORMANCE LEVEL



HD-AGRI GREASE meets the following standards:

- DIN - 51502 : KP 2 N-30

IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com.