



MOTUL HD 80W-90



Gearbox and differential lubricant
Gearbox and differential lubricant
Extreme Pressure
Mineral

TYPE OF USE

HD 80W-90 is an Extreme Pressure gearbox and differential lubricant.

PERFORMANCES

MOTUL HD ist ein hochwertiges mineralisches Hypoidgetriebeöl für Schaltgetriebe, Achsantriebe, Lenk- und Verteilergeltriebe für hohe mechanische und thermische Belastungen. BESONDERE VORTEILE Auch für höhere Drücke im Getriebe geeignet. Verhindert Korrosion und schäumt nicht. Mindert die Reibung und verhindert Verschleiß. Neutral gegen Dichtungen und Synchronringe. Alterungsbeständig

RECOMMENDATIONS

Oil drains: refer to manufacturers' recommendations and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE J 300	80W-90
Density at 20°C (68°F)		0.890
Viscosity at 40°C (104°F)	ASTM D445	144.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	15.0 mm ² /s
Viscosity Index	ASTM D2270	105.0
Pour point	ASTM D97	-27.0 °C / -16.0 °F
Flash point	ASTM D92	210.0 °C / 410.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

09/25



MOTUL HD 80W-90



Gearbox and differential lubricant
Gearbox and differential lubricant
Extreme Pressure
Mineral

STANDARDS	
API	GL-4, GL-5
MIL-L	2105 D