



MOTUL HD COOL POWER

High performance engine cooling liquid

Ready to use Cooling Fluid

DESCRIPTION

HD COOL POWER is an organic acid coolant formulated with carboxylate for superior performance and long life.

HD COOL POWER is designed for use in all types of engines including automotive, heavy duty diesel, on and off highway, stationary power generation and marine.

APPLICATIONS

HD COOL POWER es un líquido refrigerante con inhibidores de ácidos orgánicos formulado con carboxilato para altas exigencias y periodos de uso largos.

HD COOL POWER está diseñado para todo tipo de motores incluyendo automoción, motores diésel para vehículos pesados, motores estacionarios y motores de uso marino.

ADVANTAGES

- Long Life protection of aluminium, copper, cast iron, steel, alloys and solder components, brass and bronze.
- Protection against cavitation erosion in wet liner applications.
- Additive stability alleviates the need for the addition of supplementary and dry coolant additives.
- Improves thermal stability.
- Improves thermal stability.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	HD COOL POWER
Color	-	Visual	Purple
Density at 20°C (68°F)	g/mL	ASTM D1122	1.058
pH	-	ASTM D1287	9.4

These characteristics are given only for information and can be updated over time.



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.