



MOTUL HD COOL POWER ULTRA



High performance engine coolant concentrate
High performance engine coolant concentrate
Concentrated cooling fluid

TYPE OF USE

HD COOL POWER ULTRA is an organic acid coolant concentrate formulated with carboxylate for superior performance and long life.

HD COOL POWER ULTRA is designed for use in all types of engines including automotive, heavy duty diesel, on and off highway, stationary for power generation and marine.

During extensive field testing, **HD COOL POWER ULTRA** has proven to provide superior protection for at least 32,000 hours in marine and stationary applications.

RECOMMENDATIONS

HD COOL POWER ULTRA must be diluted in de-mineralized water for use as coolant.

- Mix with 8% **HD COOL POWER ULTRA** and 92% correct demineralised water.
- Do not use undiluted.
- Can be mixed with EG/PG for freeze point protection where required.
- For off-highway, power generation applications or high coolant volume circuits please see the OEM's engine de rate charts for glycol content percentages.

PROPERTIES

Color	Visual	Purple
Density at 20°C (68°F)	ASTM D1122	g/mL 1.058
pH	ASTM D1287	9.4

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

04/25



High performance engine coolant concentrate
High performance engine coolant concentrate
Concentrated cooling fluid

OEM PERFORMANCES	
CATERPILLAR	MAK
DETROIT DIESEL	DFS93K217
DEUTZ	0199-99-2091 / 12
Innio Jenbacher	TA 1000-0204
LIEBHERR	MD1-36-130
MAN	Diesel B&W 2 and 4 stroke, Diesel B&W AG – D36 5600, 248
MTU	MTL 5049
MWM	0199-99-2091 / 12
WÄRTSILÄ	Diesel, gas, dual fuel engines
WAUKESHA	
YANMAR	
PRODUCTS	
Mercedes-Benz Truck	MB 312.0
NSD	TR 1508 – 10/94
Rolls Royce Bergen	2.13.01 – diesel and gas engines
SACM DIESEL	DLP799861
Semt Pielstick	

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.