



## MOTUL HD COOL POWER ULTRA

High performance engine coolant concentrate

Concentrated Cooling Fluid

### DESCRIPTION

**HD COOL POWER ULTRA** is an organic acid coolant concentrate formulated with carboxylate for superior performance and long life.

**HD COOL POWER ULTRA** is designed for use in all types of engines including automotive, heavy duty diesel, on and off highway, stationary for power generation and marine.

During extensive field testing, **HD COOL POWER ULTRA** has proven to provide superior protection for at least 32,000 hours in marine and stationary applications.

### ADVANTAGES

- Long Life protection of aluminium, copper, cast iron, steel, alloys and solder components, brass and bronze.
- Protection against cavitation erosion in wet liner applications.
- Additive stability alleviates the need for the addition of supplementary and dry coolant additives.
- Improves thermal stability.
- Glycol free formulation for optimum heat transfer.

### TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	HD COOL POWER ULTRA
Color	-	Visual	Purple
Density at 20°C (68°F)	g/mL	ASTM D1122	1.058
pH	-	ASTM D1287	8.2

These characteristics are given only for information and can be updated over time.



## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

### Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on [www.motul.com](http://www.motul.com).

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.