



MOTUL HD COOL POWER ULTRA



High performance engine coolant concentrate
High performance engine coolant concentrate
Concentrated cooling fluid

CONSEILS D'UTILISATIONS

HD COOL POWER ULTRA est un liquide de refroidissement concentré à base d'acide organique formulé avec du carboxylate pour des performances supérieures et une longue durée de vie.

HD COOL POWER ULTRA a été développé pour tout type de moteur incluant les moteurs automobiles, diesel poids lourds, sur et hors-route, les moteurs stationnaires et marins.

RECOMMANDATIONS

HD COOL POWER ULTRA must be diluted in de-mineralized water for use as coolant.

- Mix with 8% **HD COOL POWER ULTRA** and 92% correct demineralised water.
- Do not use undiluted.
- Can be mixed with EG/PG for freeze point protection where required.
- For off-highway, power generation applications or high coolant volume circuits please see the OEM's engine de rate charts for glycol content percentages.

PROPRIÉTÉS

Couleur	Visuel	Pourpre
Densité à 20°C	ASTM D1122	g/mL 1.058
pH	ASTM D1287	8.2



High performance engine coolant concentrate
High performance engine coolant concentrate
Concentrated cooling fluid

OE - PERFORMANCE	
CATERPILLAR	MAK
DETROIT DIESEL	DFS 93K217
DEUTZ	0199-99-2091 / 12
Innio Jenbacher	TA 1000-0204
LIEBHERR	MD1-36-130
MAN	Diesel B&W 2 and 4 stroke, Diesel B&W AG – D36 5600, 248
MTU	MTL 5049
MWM	0199-99-2091 / 12
WÄRTSILÄ	Diesel, gas, dual fuel engines
WAUKESHA	
YANMAR	
PRODUITS	
Mercedes-Benz Truck	MB 312.0
NSD	TR 1508 – 10/94
Rolls Royce Bergen	2.13.01 – diesel and gas engines
SACM DIESEL	DLP799861
Semt Pielstick	