



HDX 80W-90

TRANSMISSION / ENGRENAGE

DESCRIPTION

All mechanical transmission, synchronized or not synchronized gearboxes, gearbox/differential, transfer gearboxes and hypoid differentials without limited slip system operating under shocks, heavy loads and low revolution speed or moderate loads and high revolution speed.

APPLICATIONS

Technosynthese® lubricant with Extreme Pressure for an efficient anti wear protection, reinforced with synthetic base stocks for a better resistance at high temperature and longer life span.

Very high lubricating power which decreases friction and wear.

SAE 90 viscosity grade at high temperature to provide outstanding oil film resistance and to reduce transmission noise.

Suitable for any type of seals and yellow materials used in gearbox designs.

Anti-corrosion, Anti-foam.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.