

HONDA HR LUB 10W-30 4T

**4 Stroke engine Lubricant for Honda engines
Lawn, Garden and Power equipment
Gasoline Engines
Technosynthese®**

TYPE OF USE

Specially formulated for 4T gasoline Honda motorised gardening tools and small farming machines.
All Gasoline 4 Stroke engines: Lawn mowers, motor mowers, grass cutters, light tractors, power generators, power pumps, blowers, snowthrowers...
Suitable for all types of fuels : leaded and unleaded gasoline, with or without Ethanol.
All types of 4 stroke engines with or without catalytic converter.

PERFORMANCES**STANDARDS**

API SL/CF

Multigrade engine oil with high detergent/dispersant and anti-wear power, reinforced with synthetic Technosynthese® base for better engine protection.
The SAE 10W-30 viscosity grade facilitates starting, reduces wear and reduces fuel consumption.
High dispersant and detergent properties to ensure better engine cleanliness, avoid ring sticking, avoid deposits and varnishes on valves and pistons. Minimizes black sludge in oil sump.
Anti-corrosion properties for a better protection during wintering.
Anti-oxidation, Anti-wear, Anti-foam properties.

RECOMMENDATIONS

Oil change: According to Honda's requirements : every 6 months or every 50 hours.
MOTUL HONDA HR LUB 4T 10W-30 can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.870

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



HONDA HR LUB 10W-30 4T

**4 Stroke engine Lubricant for Honda engines
Lawn, Garden and Power equipment
Gasoline Engines
Technosynthese®**

Viscosity at 40°C (104°F)	ASTM D445	66.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.6 mm ² /s
Viscosity Index	Visual	149.0
Pour point	ASTM D97	-30.0 °C / -22.0 °F
TBN	ASTM D2896	8.0 mg KOH/g
Flash point	ASTM D92	226.0 °C / 439.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

03/23