DATA SHEET

MOTUL INUGEL 5110 -35°C

READY TO USE FLUID

DESCRIPTION

MOTUL INUGEL 5110 is a ready to use cooling liquid based on monoethyleneglycol, using an organic/non organic mix technology, named Hybrid technology, in order to meet the requirements of B71 5110 standard recommended by the PSA Group: PEUGEOT, CITROËN and DS.
This product can be mixed with coolants based on ethylene glycol.
Especially recommended for all cooling systems of PSA (Peugeot, Citroën and DS) vehicles.

APPLICATIONS

Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.
Meets the requirements of PSA norm B71 5110 for PEUGEOT, CITROËN and DS cooling liquid.
Optimal and long lasting protection from freezing and from corrosion of the cooling system and metallic parts. Optimum protection of aluminum at high temperatures.
Provides excellent thermal exchange and therefore improves engine cooling efficiency.
Seals, hoses, pipes and plastic parts friendly.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice
All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.
Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.

The environmental, health and safety requirements are mentioned on the safety data sheet that is available at www.quickfds.fr