

## IRIX FIFTH WHEEL GREASE

Mineral Base

### DESCRIPTION

IRIX FIFTH WHEEL GREASE is a Technosynthese anti-seizing grease for semi-trailer fifth wheels

### ADVANTAGES

- High resistance to water according to DIN 51 807 T1.
- Stay in place performance - high adhesiveness.
- Anti-corrosion protection.
- High temperature stability.
- High temperature stability.
- Reinforced with Graphite: Formation of solid lubricant layers.

### TECHNICAL CHARACTERISTICS

CHARACTERISTICS	METHOD	IRIX FIFTH WHEEL GREASE
Color	Visual	Black
Drop point	ASTM D2265	190 °C
Base oil viscosity at 40°C	DIN 51562	800.0 mm <sup>2</sup> /s
Base oil viscosity at 100°C	DIN 51562	65.0 mm <sup>2</sup> /s
Consistency grade	DIN 51818	NLGI 2
4 Ball test - Wear scar	DIN 51350:4	< 0.8 mm
TIMKEN Test - Load	ASTM D2509	222.5 N
Copper Strip Corrosion	ASTM D4048	1 / 100
Water washout	DIN 51807 T1	1 / 90



## STANDARDS / APPROVALS / PERFORMANCE LEVEL

**IRIX FIFTH WHEEL GREASE** meets the following standards:

- DIN - 51502 : KPF 2 N-30

## IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on [www.motul.com](http://www.motul.com).

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.