



IRIX FIFTH WHEEL GREASE

Mineral Base

DESCRIPTION

IRIX FIFTH WHEEL GREASE is a Technosynthese anti-seizing grease for semi-trailer fifth wheels

ADVANTAGES

- High resistance to water according to DIN 51 807 T1.
- Stay in place performance - high adhesiveness.
- Anti-corrosion protection.
- High temperature stability.
- High temperature stability.
- Reinforced with Graphite: Formation of solid lubricant layers.

TECHNICAL CHARACTERISTICS

| CHARACTERISTICS | METHOD | IRIX FIFTH WHEEL GREASE |
|-----------------------------|--------------|--------------------------|
| Color | Visual | Black |
| Drop point | ASTM D2265 | 190 °C |
| Base oil viscosity at 40°C | DIN 51562 | 800.0 mm ² /s |
| Base oil viscosity at 100°C | DIN 51562 | 65.0 mm ² /s |
| Consistency grade | DIN 51818 | NLGI 2 |
| 4 Ball test - Wear scar | DIN 51350:4 | < 0.8 mm |
| TIMKEN Test - Load | ASTM D2509 | 222.5 N |
| Copper Strip Corrosion | ASTM D4048 | 1 / 100 |
| Water washout | DIN 51807 T1 | 1 / 90 |



STANDARDS / APPROVALS / PERFORMANCE LEVEL

IRIX FIFTH WHEEL GREASE meets the following standards:

- DIN - 51502 : KPF 2 N-30

IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.