



IRIX FIFTH WHEEL GREASE

Graisse
Grease for semi-trailer fifth wheels
Semi-synthetic - NLGI 2

TYPE OF USE

IRIX FIFTH WHEEL GREASE is a Technosynthese anti-seizing grease for semi-trailer fifth wheels

PERFORMANCES

High performance grease formulated to provide outstanding protection and stay in place performance in heavily-loaded, harsh operating environments specific to fifth-wheel hitches used in trucking and trailer applications.

Can be also used for the greasing of cables, open gears, ring gears, gear-racks and ball joints for civil engineering machinery.

Operating temperature for long term lubrication: from -30°C / -22°F to +140°C / +284°F.

PROPERTIES

Color	Visual	Black
Drop point		190 °C
	ASTM D2265	
	Å	
Base oil viscosity at 40°C	DIN 51562	800.0 mm²/s
Base oil viscosity at 100°C	DIN 51562	65.0 mm²/s
Consistency grade	DIN 51818	NLGI 2
4 Ball test - Wear scar	DIN 51350:4	< 0.8 mm
TIMKEN Test - Load	ASTM D2509	222.5 N
Copper Strip Corrosion	ASTM D4048	1 / 100
Thickener		Lithium soap
Water washout	DIN 51807 T1	1 / 90

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com

09/25



IRIX FIFTH WHEEL GREASE

Graisse
Grease for semi-trailer fifth wheels
Semi-synthetic - NLGI 2

STANDARDS	
DIN	51502 : KPF 2 N-30

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

motul.com