

IRIX FIFTH WHEEL GREASE**Grease for semi-trailer fifth wheels
Technosynthese® - NLGI 2****CONSEILS D'UTILISATIONS**

IRIX FIFTH WHEEL GREASE is a Technosynthese anti-seizing grease for semi-trailer fifth wheels

PERFORMANCES**NORMES** DIN 51502 : KPF 2 N-30

High performance grease formulated to provide outstanding protection and stay in place performance in heavily-loaded, harsh operating environments specific to fifth-wheel hitches used in trucking and trailer applications.

Can be also used for the greasing of cables, open gears, ring gears, gear-racks and ball joints for civil engineering machinery.

Operating temperature for long term lubrication: from -30°C / -22°F to +140°C / +284°F.

PROPRIÉTÉS

Couleur	Visuel	Noir
Point de goutte	ASTM D2265	190 °C
Viscosité de l'huile de base à 40°C	DIN 51562	800.0 mm ² /s
Viscosité de l'huile de base à 100°C	DIN 51562	65.0 mm ² /s
Grade de consistance	DIN 51818	NLGI 2
Test 4-billes usure	DIN 51350:4	< 0.8 mm
Essai TIMKEN - charge	ASTM D2509	222.5 N
Cotation lame de cuivre	ASTM D4048	1 / 100
Résistance au délavage	DIN 51807 T1	1 / 90