



MOTULTECH IRIX HP-HIGH TEMP 250 CL

Chain Oil - High Temperature

DESCRIPTION

IRIX HP - HIGH TEMP HE CL is a 100% synthetic oil formulated from new generation esters and anti-oxidant additives.

APPLICATIONS

IRIX HP - HIGH TEMP HE CL is specifically adapted to the lubrication of chains and bearings of installations with a continuous temperature between 150 and 300 °C:

- Chains and textile range sliding tracks.
- Chains and continuous press rolls for particle boards.
- Chains and bearings in a drying cabinet, polymerising tunnel, glass wool or gypsum board dryer.

ADVANTAGES

- Can be used up to 300 °C
- Low evaporation
- Excellent resistance to Thermal Oxidation and Coking
- High lubricating and Extreme Pressure Properties
- Resistance to corrosion
- Excellent adhesion

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	IRIX HP-H.TEMP 250CL
Evaporation	%	ASTM D972	1.0 204 °C / 6.5 h

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.



Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.