



MOTUL IRIX L 130-2

Greases

DESCRIPTION

IRIX L 130-2 is a multi-purpose, extreme-pressure grease formulated from premium mineral base oils and a Lithium thickener. The NLGI grade 2 makes it suitable for a wide range of general-purpose applications.

APPLICATIONS

IRIX L 130-2 is suitable for a wide range of general-purpose lubrication applications ranging from bearings to cables, chains and other linkages. Also suitable as a multipurpose chassis, pin and bushing grease.

Classification:

- ISO 12924: L-XBCHB2
- DIN 51502: KP2K-20

ADVANTAGES

- Excellent protection against corrosion.
- Excellent extreme-pressure performance.
- Excellent wear protection.
- Very good adhesion.
- Very good stability in service and storage.
- Insoluble in water.

**TECHNICAL INFORMATION**

TECHNICAL CHARACTERISTICS	UNITS	METHOD	IRIX L 130-2
Base oil	-		
Color	-	Visual	Amber
Texture	-		Smooth
Thickener	-		
NLGI Grade	-	ASTM D217	2
Dropping point	°C	IP 396	190.0
Base oil viscosity at 40°C	mm ² /s	ASTM D7152	130.0
Base oil viscosity at 100°C	mm ² /s	ASTM D7152	11.0
Penetration 60 strokes	1/10 mm	ISO 2137	280
EMCOR distilled water	-	ISO 11007	0-0
EMCOR salt water	-	ISO 11007	< 2-2
Water resistance at 90°C	-	DIN 51807:1	0-90
4 Ball test - Weld load	kg	ASTM D2596	285
Temperature range	-		-20°C to +140°C

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.